



**LED UPLIGHTERS**



## Adole LED Uplighters

### General Specifications

Mounting Type	Recessed
Limited Warranty	2 Years
Beam Angle	30 Degrees
Lighting Source Type	COB LED

### Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Housing Shape	Round
Surface Finish	Glossy
Driver Type	Integrated

### Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+
Mean Time Between Failure	21,900 Hrs

### Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

### Safety Features

Ingress Protection	IP68
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Impact Protection	IK07
Open Circuit Protection	Yes

### Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 90%
Vibrations	1G

## HOW TO ORDER

HUB - ADOLE - 12W - 6050K

Input Power	1	Colour Temperature (CCT)	2
3W :	3W	2732K :	2700K - 3200K
6W :	6W	4050K :	4000K - 5000K
12W :	12W	6050K :	6000K - 6500K
18W :	18W		
24W :	24W		
36W :	36W		

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - ADOLE - 12W - 6050K**



## Getto LED Uplighters

### General Specifications

Mounting Type	Recessed
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

### Fixture Specifications

Housing Material	Stainless Steel
Diffuser Material	Polycarbonate

### Performance Specifications

Rated LED Burning Hours	50,000 Hrs
Start up time	Instant

### Electrical Specifications

Input Frequency	NA
-----------------	----

### Safety Features

Ingress Protection	IP68
Short Circuit Protection	NA
Impact Protection	IK07
Open Circuit Protection	Yes
Over Voltage Protection	Yes

### Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 100%
Vibrations	1G

## HOW TO ORDER

HUB - GETTO -

7W

6050K

Input Power	1	Colour Temperature (CCT)	2
1W :	1W	2732K :	2700K - 3200K
3W :	3W	4050K :	4000K - 5000K
7W :	7W	6050K :	6000K - 6500K
12W :	12W		
20W :	20W		
30W :	30W		
40W :	40W		

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - GETTO - 7W - 6050K**



## Vendo LED Uplighters

### General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

### Fixture Specifications

Housing Material	Stainless Steel
Diffuser Material	Polycarbonate
Housing Shape	Round
Surface Finish	Glossy
Driver Type	External

### Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

### Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

### Safety Features

Ingress Protection	IP68
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes

### Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	Upto 100%
Vibrations	1G

## HOW TO ORDER

HUB - VENDO -

18W

4050K

Input Power	1	Colour Temperature (CCT)	2
9W :	9W	6050K :	6000K - 6500K
18W :	18W	RD :	Red
24W :	24W	RD :	Red
		2732K :	2700K - 3200K
		GR :	Green
		GR :	Green
		BL :	Blue
		4050K :	4000K - 5000K

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - VENDO - 18W - 4050K**