



Avera 1 LED Bendable Linear Lights

General Specifications

Mounting Type	Pole
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	COB LED

Fixture Specifications

Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Black
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	120 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 90%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 10KV
440V Withstand Duration	Yes
External Surge Protection @ 10KV	Yes
Short Circuit Protection	Yes
Open Circuit Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

HOW TO ORDER

HUB - AVERA1 - 50W - 4050K

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - AVERA 1 - 50W - 4050K