HUBLIT

Polycarbonate



HOW TO ORDER

HUB - AVERA1_CL ONE₁

30W

2732K

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example: HUB - AVERA 1_CLONE1 - 30W - 2732K

Avera 11 LED Street Lights

General	Specification	าร
---------	----------------------	----

Mounting Type Pole Limited Warranty 2 Years 120 Degrees Beam Angle COB LED Lighting Source Type

Fixture Specifications

Diffuser Material

Surface Finish Powder Coated Housing Colour Black Driver Type Integrated

Performance Specifications

Colour rendering index (CRI) 70+ Rated LED Burning Hours 50,000 Hrs Colour Temperature (CCT) 6000K - 6500K Start up time Instant Efficacy (Lm / W) 100+

Electrical Specifications

Input Voltage (VAC) 120 - 270 VAC Total Harmonic Distorsion Upto 10% Input Frequency 50 Hz Power Factor 0.95 +Driver Efficiency Upto 90%

Safety Features

Ingress Protection IP65 Surge Protection Upto 10KV 440V Withstand Duration Yes External Surge Protection @ 10KV Yes Short Circuit Protection Yes Open Circuit Protection Yes

Environmental Specification

Working Temperature 0 to 40 C Vibrations 1G

