



Diplo LED Spot Lights

General Specifications

Mounting Type	Recessed
Limited Warranty	2 Years
Lighting Source Type	COB LED

Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Driver Type	External

Performance Specifications

Colour rendering index (CRI)	80+
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 - 60 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP20
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

HOW TO ORDER

HUB - DIPLO - 40W - 4050K

Input Power	1	Colour Temperature (CCT)	2
12W :	12W	2732K :	2700K - 3200K
20W :	20W	4050K :	4000K - 5000K
30W :	30W	6050K :	6000K - 6500K
40W :	40W		

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - DIPLO - 40W - 4050K