



Englo LED Surface/Suspended Linear Task Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Lighting Source Type	SMD LED

Fixture Specifications

Housing Material	Extruded Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Anodised
Driver Type	External

Performance Specifications

Colour rendering index (CRI)	80+
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 to 60 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP44
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

Mechanical Specifications

Luminaire Dimension (L X W X H)	13mm X 16mm
---------------------------------	-------------

HOW TO ORDER

HUB - ENGLO - 1W/F - BL - 4050K

Input Power	1	Housing Colour	2
1W/F : 1W/F		GR : Grey	
		WH : White	
		BL : Black	

Colour Temperature (CCT)	3
2732K : 2700K - 3200K	
4050K : 4000K - 5000K	
6050K : 6000K - 6500K	

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - ENGLO - 1W/F - BL - 4050K