



## Esita LED Spot Lights

### General Specifications

Mounting Type	Suspended
Limited Warranty	2 Years
Beam Angle	30 Degrees
Lighting Source Type	COB LED

### Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Driver Type	Integrated

### Performance Specifications

Colour rendering index (CRI)	80+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

### Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

### Safety Features

Ingress Protection	IP20
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes

### Packaging Specifications

Luminaries Per Box	1
--------------------	---

### Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	Upto 80%
Vibrations	1G

## HOW TO ORDER

**HUB** - **ESITA** - **20W** - **BL** - **2732K**

Input Power	1	Housing Colour	2
<b>5W :</b> 5W		<b>WH :</b> White	
<b>10W :</b> 10W		<b>BL :</b> Black	
<b>20W :</b> 20W			
<b>30W :</b> 30W			

Colour Temperature (CCT)	3
<b>2732K :</b> 2700K - 3200K	
<b>4050K :</b> 4000K - 5000K	
<b>6050K :</b> 6000K - 6500K	

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - ESITA - 20W - BL - 2732K**