



Etion LED Tube Lights

General Specifications

| | |
|----------------------|-------------|
| Mounting Type | Retrofit |
| Limited Warranty | 2 Years |
| Beam Angle | 120 Degrees |
| Lighting Source Type | SMD LED |

Fixture Specifications

| | |
|-------------------|--------------------|
| Housing Material | Extruded Aluminium |
| Diffuser Material | Polycarbonate |
| Surface Finish | Anodised |
| Housing Colour | Grey |
| Driver Type | Integrated |

Performance Specifications

| | |
|-------------------------|------------|
| Rated LED Burning Hours | 50,000 Hrs |
| Start up time | Instant |
| Efficacy (Lm / W) | 100+ |

Electrical Specifications

| | |
|---------------------------|---------------|
| Input Voltage (VAC) | 150 - 270 VAC |
| Total Harmonic Distorsion | Upto 20% |
| Input Frequency | 50 Hz |
| Power Factor | 0.90 + |
| Driver Efficiency | Upto 90% |

Safety Features

| | |
|--------------------------|----------|
| Ingress Protection | IP20 |
| Surge Protection | Upto 2KV |
| Short Circuit Protection | Yes |
| Open Circuit Protection | Yes |

Environmental Specification

| | |
|---------------------|-----------|
| Working Temperature | 0 to 40 C |
| Vibrations | 1G |

HOW TO ORDER

HUB - **ETION** - **18W** - **MW** - **4050K**

| | | | |
|------------------|---|------------------------------|---|
| Input Power | 1 | Motion Sensing | 2 |
| 18W : 18W | | PIR : Infrared Sensor | |
| | | MW : Microwave Sensor | |

| | |
|------------------------------|---|
| Colour Temperature (CCT) | 3 |
| 2732K : 2700K - 3200K | |
| 4050K : 4000K - 5000K | |
| 6050K : 6000K - 6500K | |

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - ETION - 18W - MW - 4050K