



Porte LED High Bay Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Lighting Source Type	COB LED

Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Black
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	70+
Start up time	Instant
Efficacy (Lm / W)	90+

Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 to 60 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

HOW TO ORDER

HUB - PORTE -

100W

6050K

Input Power	1	Colour Temperature (CCT)	2
50W : 50W		2732K : 2700K - 3200K	
60W : 60W		4050K : 4000K - 5000K	
100W : 100W		6050K : 6000K - 6500K	
120W : 120W			
150W : 150W			
180W : 180W			

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - PORTE - 100W - 6050K