



Sland LED Street Lights

General Specifications

Mounting Type	Pole
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

Fixture Specifications

Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Grey
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	80+
Rated LED Burning Hours	50,000 Hrs
Colour Temperature (CCT)	6000K - 6500K
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP66
Surge Protection	Upto 10KV
440V Withstand Duration	Yes
External Surge Protection @ 10KV	Yes
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

HOW TO ORDER

HUB - SLAND -

100W

4050K

Input Power	1	Colour Temperature (CCT)	2
30W :	30W	2732K :	2700K - 3200K
50W :	50W	4050K :	4000K - 5000K
100W :	100W	6050K :	6000K - 6500K
150W :	150W		
200W :	200W		

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - SLAND - 100W - 4050K